



# A fast strategy to sequentially separate and determine $^{90}\text{Sr}$ , $^{210}\text{Pb}$ and $^{210}\text{Po}$ in water samples using Sr resin

J. Martínez<sup>1</sup> · M. de los Cobos<sup>1</sup> · A. Peñalver<sup>1</sup> · C. Aguilar<sup>2</sup> · F. Borrull<sup>1</sup>

Received: 28 September 2021 / Accepted: 28 October 2021 / Published online: 9 December 2021  
© The Author(s) 2021

## Abstract

This study presents a rapid and novel sequential separation strategy based on extraction chromatography for determining  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  in drinking water samples. It involves the use of Sr resin for the separation and then liquid scintillation counting and alpha spectrometry for the determination. The experimental results obtained showed that the proper acidic solution to quantitatively retain the aforementioned radionuclides is 3 M  $\text{HNO}_3$ . The optimum eluents were determined for obtaining quantitative recoveries (70–80%) of  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$ . The method was validated with intercomparison water samples and is satisfactory in terms of minimum detectable activities, which are 50% lower than that established in RD 314/2016.

**Keywords** Strontium-90 · Lead-210 · Polonium-210 · Sr resin · Drinking water · Sequential separation

## Introduction

Water intended for human consumption is generally treated for potabilization, with various parameters being routinely controlled to ensure its quality and safe distribution to the population as described in European Directive (EU) 2020/2184 [1]. Of these parameters, one of the most important is the evaluation of the drinking water's radiological quality.

In Spain, control of the radioactive substances present in water intended for human consumption and their screening level requirements is performed in accordance with Royal Decree 314/2016 [2], which was transposed from Council Directive 2013/51/Euratom [3]. The Decree requires the total indicative dose (ID) to be assessed, and to this end the activity of certain artificial and natural radionuclides needs

to be determined. Different radionuclide activities have to be determined in different situations, such as when the gross alpha index activity exceeds  $0.1 \text{ Bq L}^{-1}$ . The present study focuses on the activity determination of three of the radionuclides specified in the legislation:  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$ .

In the literature there are various approaches in which these radionuclides have been determined in environmental water samples [4–6]. These strategies generally include a radiochemical separation, which is mandatory as sample pretreatment to avoid measurement interferences [5, 7, 8]. The authors of these approaches have usually focused on determining a single radionuclide or in some cases two. However, it is important to stress that the development of sequential radiochemical strategies to separate more radionuclides is of great interest, since it could be very useful in shortening the analysis time. The development of extraction chromatographic resins has contributed notably to enabling radionuclide separation/isolation.

Sr resin has become one of the most popular resins for isolating  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  prior to their measurement. In the literature, as can be seen in Table 1, there are a number of Sr resin based strategies that individually separate one of these three radionuclides [8–10] or even isolate two of them – e.g.  $^{90}\text{Sr}$  and  $^{210}\text{Pb}$  [11–13],  $^{90}\text{Sr}$  and  $^{210}\text{Po}$  [14] or  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  [5, 7, 15–21] – in different kinds of matrices. The table shows the load sample, resin conditioning media and radionuclide elution media used, these being the main parameters that may have an influence on recovery.

✉ F. Borrull  
francesc.borrull@urv.cat

<sup>1</sup> Departament de Química Analítica i Química Orgànica, Universitat Rovira i Virgili, Unitat de Radioquímica Ambiental i Sanitària (UR AIS), Consorci d'Aigües de Tarragona (CAT), Carretera Nacional 340, Km. 1094, 43895 l'Ampolla Tarragona, Spain

<sup>2</sup> Serra Hünter Professor, Departament de Química Analítica i Química Orgànica, Universitat Rovira i Virgili, Unitat de Radioquímica Ambiental i Sanitària (UR AIS), Consorci d'Aigües de Tarragona (CAT), Carretera Nacional 340, Km. 1094, 43895 l'Ampolla Tarragona, Spain

**Table 1** Summary of different strategies using Sr resin reported in the literature

|   | Matrix  | Load sample and resin conditioning media | Radionuclide elution media   | % recovery     | References |
|---|---|--|--|----------------|------------|
| $^{90}\text{Sr}$                        | NPP spent ion-exchange resin                                      | 8 M $\text{HNO}_3$                       | 0.05 M $\text{HNO}_3$  | 99             | [9]        |
| $^{210}\text{Pb}$                       |   | 0.01 – 8 M $\text{HNO}_3$                | n.s  | n.s            | [8]        |
| $^{210}\text{Po}$                       | Wild bilberries   | 8 M $\text{HNO}_3$                       | 8 M $\text{HNO}_3$ , 3 M $\text{HNO}_3$ – 0.05 M $\text{C}_2\text{H}_2\text{O}_4$ , 3 M $\text{HNO}_3$   | > 50           | [10]       |
| $^{90}\text{Sr}$ and $^{210}\text{Pb}$  | Sludge  | 2 M $\text{HNO}_3$                       | $^{90}\text{Sr}$ 0.02 M $\text{HNO}_3$<br>$^{210}\text{Pb}$ 0.06 M $(\text{NH}_4)_2\text{C}_2\text{O}_4$   | 90<br>98       | [11]       |
|   | Marine macroalgae and mussels                                     | 3 M $\text{HNO}_3$                       | $^{90}\text{Sr}$ 0.05 M $\text{HNO}_3$<br>$^{210}\text{Pb}$ 6 M $\text{HCl}$   | 75–85<br>73–85 | [12]       |
|   | Freshwater fish   | 8 M $\text{HNO}_3$                       | $^{90}\text{Sr}$ 0.05 M $\text{HNO}_3$<br>$^{210}\text{Pb}$ 0.1 M $(\text{NH}_4)_2\text{C}_2\text{O}_4$  | 56–94<br>50–88 | [13]       |
| $^{90}\text{Sr}$ and $^{210}\text{Po}$  | Sea urchins, mussels and oysters                                  | 8 M $\text{HNO}_3$                       | $^{90}\text{Sr}$ 0.05 M $\text{HNO}_3$<br>$^{210}\text{Po}$ 8 M $\text{HNO}_3$ , 3 M $\text{HNO}_3$ – 0.05 M $\text{C}_2\text{H}_2\text{O}_4$ , 3 M $\text{HNO}_3$ | 53–75<br>> 50  | [14]       |
| $^{210}\text{Pb}$ and $^{210}\text{Po}$ | Soil, phosphate rock and phosphogypsum                            |  | $^{210}\text{Pb}$ 6 M $\text{HCl}$   | 60–80          | [7, 15–17] |
|   | Ca-rich ash samples   | 2 M $\text{HCl}$                         |  |                |            |
|   | Sediment, seaweed and phosphate ore                               |  | $^{210}\text{Po}$ 6 M $\text{HNO}_3$   | 50–70          |            |
|   | Water   |  |  |                |            |
|   | Shrimp and clam   | 2 M $\text{HCl}$                         | $^{210}\text{Pb}$ 0.1 M $(\text{NH}_4)_2\text{C}_2\text{O}_4$<br>$^{210}\text{Po}$ 1 M $\text{HNO}_3$ and 0.1 M $\text{HNO}_3$                                     | 72<br>86       | [18]       |
|   | Soil, sediment, shellfish and seaweed                             | 4 M $\text{HCl}$                         | $^{210}\text{Pb}$ 8 M $\text{HCl}$<br>$^{210}\text{Po}$ 6 M $\text{HNO}_3$   | 95<br>55–99    | [19]       |
|   | $^{210}\text{Pb}$ – $^{210}\text{Bi}$ – $^{210}\text{Po}$ mixture | 8 M $\text{HCl}$                         | $^{210}\text{Pb}$ 8 M $\text{HCl}$<br>$^{210}\text{Po}$ 0.1 M $\text{HNO}_3$   | n.s<br>n.s     | [20]       |
|   | Plants  | 3 M $\text{HNO}_3$                       | $^{210}\text{Pb}$ 0.05 $\text{C}_6\text{H}_{11}\text{NO}_7$<br>$^{210}\text{Po}$ 8 M $\text{HNO}_3$  | 67–74<br>n.s   | [21]       |

n.s. not specified

It can be observed that acidic conditions are commonly used in the conditioning and sample loading steps. Authors generally use  $\text{HNO}_3$  or  $\text{HCl}$  at different concentrations for this purpose. In the case of  $^{90}\text{Sr}$ , its affinity with the resin reaches maximum values at between 3 and 8 M  $\text{HNO}_3$  [9]. However, as previously stated in the literature [22], hydrochloric acid media are useless in terms of strontium extraction because de-solvating strontium chloride neutral species is more difficult than de-solvating neutral nitrate species formed using nitric acid.

As regards  $^{210}\text{Pb}$ , this radionuclide presents a high retention in nitric acid (0.1 – 8 M) and hydrochloric acid (0.1 – 2 M) media [18, 23]. Similarly,  $^{210}\text{Po}$  is highly retained in 1 M  $\text{HNO}_3$  [23], despite the fact that high recoveries were also achieved in other conditions, such as stronger nitric acid concentrations (8 M  $\text{HNO}_3$ ) and in a wide range of  $\text{HCl}$  concentrations [5]. It can therefore

be concluded that both the composition of the conditioning solvent and the sample loading solution are important because they have a notable effect on the selectivity and retention capacity of each radionuclide on the resin.

The aim of this study is to present for the first time a strategy to sequentially separate and then determine three radionuclides— $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$ —using the Sr resin. To this end the various experimental conditions that may have an effect on the efficacy of the retention of the radionuclides in that resin are evaluated. This approach will be useful in minimizing the turnaround time needed to separate and determine the radionuclides and can therefore be used in situations that call for a quick response, especially when determining those radionuclides that contribute to the indicative dose estimation (RD 314/2016) in drinking water samples. Finally, the method is tested and

validated by analysing water samples from intercomparison exercises.

## Experimental part

### Reagents and instruments

All the chemical reagents and solutions used in this study were of analytical grade. HCl (35%) and HNO<sub>3</sub> (65%) were supplied by J.T. Baker (Deventer, Holland). Ammonium oxalate and ascorbic acid were supplied by Chem-Lab (Zedelgem, Belgium) and Panreac (Darmstadt, Germany). Strontium nitrate and lead nitrate were supplied by Fluka Chemie GmbH (Switzerland) and Probus (Barcelona, Spain) respectively.

Sr resin (100–150 μm, 2 mL columns) and a 12-hole vacuum box were supplied by TrisKem International (France) and were used for the radiochemical separation of <sup>90</sup>Sr, <sup>210</sup>Pb and <sup>210</sup>Po. The extractant used in Sr resin is a crown-ether (4,4'-(5')-di-tert-butylcyclohexane-18-crown-6) diluted in 1-octanol.

The liquid scintillation (LS) cocktail, Optiphase HiSafe 3, and polyethylene (PE) scintillation vials used to prepare the <sup>90</sup>Sr and <sup>210</sup>Pb samples were supplied by PerkinElmer (Waltham, USA) and Sarstedt (Nümbrecht, Germany) respectively. To determine these radionuclides an ultra-low-background Quantulus 1220™ liquid scintillation spectrometer (PerkinElmer) was used. It was equipped with three sample tray tables with 20 positions and the EASY view spectrum analysis programme.

<sup>210</sup>Po was auto-deposited on silver disks supplied by Goodfellow (Huntingdon, United Kingdom) and determined by alpha spectrometry (EG&G ORTEC, 676 Model, USA), which includes an ion-implanted silicon detector (ORTEC, size: 450 mm<sup>2</sup>; alpha resolution: 25 keV FWHM at 5.48 MeV of <sup>241</sup>Am) in a vacuum chamber (Edwards, Model E2M8), a detector bias supplier, a preamplifier, a linear preamplifier and a multichannel pulse height analyser.

The standard solutions of <sup>90</sup>Sr/<sup>90</sup>Y, <sup>210</sup>Pb/<sup>210</sup>Bi/<sup>210</sup>Po and <sup>209</sup>Po used for the method optimization were provided by CIEMAT (Madrid, Spain) and Eckert & Ziegler (Valencia, California). The certified nominal activity for <sup>90</sup>Sr/<sup>90</sup>Y was 246.7 ± 0.3 Bq g<sup>-1</sup>, for <sup>210</sup>Pb/<sup>210</sup>Bi/<sup>210</sup>Po it was 580 ± 10 Bq g<sup>-1</sup> and for <sup>209</sup>Po it was 100 ± 15 Bq g<sup>-1</sup>.

An inductively coupled plasma mass spectrometry (ICP-MS) Elan DRC-e (Perkin Elmer, Spain) was used to calculate the recovery of the sequential separation process for the stable strontium and lead. The system was fitted with a Scott spray chamber and a crossflow nebulizer (Perkin Elmer, Spain). <sup>71</sup>Ga and <sup>205</sup>Tl were used as internal standards to compensate for instrument drift between runs.

### Batch studies

The chromatographic capacity factor ( $k'$ ) for the Sr resin for the radionuclides under study was determined. The procedure used was as follows.

First, 10 mL solutions containing 0.5 mL of Sr(II) and Pb(II) solutions (1000 ppm respectively) and 1 mL of <sup>209</sup>Po (5039 Bq L<sup>-1</sup>) at the appropriate HNO<sub>3</sub> molarity (3 M) were shaken for 24 h with 0.15 g of Sr resin. Blank samples were also measured. The samples were then filtered using a syringe and a 0.45 μm cellulose filter. The Sr(II) and Pb(II) present in the nitric phase were determined by ICP-MS, while <sup>209</sup>Po activity was determined by LSC.

From this batch study, the weight distribution value ( $D_w$ ) of the Sr resin can be calculated by determining the radionuclide activity in the case of <sup>209</sup>Po or the element concentration in the case of Sr(II) and Pb(II), in solution before and after their contact with the Sr resin. This is done using Eq. 1 [24]:

$$D_w = \frac{A_0 - A_s}{A_s} \times \frac{V}{m} \quad (1)$$

where  $A_0$  is the initial element activity (Bq mL<sup>-1</sup>) or concentration (mg L<sup>-1</sup>),  $A_s$  is the final element activity (Bq mL<sup>-1</sup>) or concentration (mg L<sup>-1</sup>) after being in contact with the Sr resin,  $V$  is the sample volume (mL), and  $m$  is the mass of Sr resin used in the batch experiment (g).

$D_w$  can then be used to obtain the chromatographic capacity factor ( $k'$  in g mL<sup>-1</sup>), which can be calculated using Eq. 2 [24]:

$$k' = D_w/f \quad (2)$$

where  $f$  is the specific conversion factor for  $D_w$  to  $k'$  for the Sr resin and has a value of 2.17 [25].

### Procedure


The procedure used to sequentially separate and determine <sup>90</sup>Sr, <sup>210</sup>Pb and <sup>210</sup>Po in water samples is composed of three steps: pretreatment of the water sample, radionuclide separation using the Sr resin, and finally measurement of <sup>90</sup>Sr and <sup>210</sup>Pb with a liquid scintillation counter and of <sup>210</sup>Po with an alpha spectrometer.

First of all a volume of 500 mL of water sample was evaporated to dryness with a sand bath, under controlled temperature to avoid polonium volatilization [5], after adding the corresponding tracers (0.5 mg of Sr(II), 0.5 mg of Pb(II) and 0.5 mL of <sup>209</sup>Po tracer at 23.46 ± 0.49 Bq L<sup>-1</sup>). The dry residue was then re-dissolved to a final volume of

10 mL with 3 M HNO<sub>3</sub> and loaded through a 2 mL column of Sr resin.

The sequential separation of <sup>90</sup>Sr, <sup>210</sup>Pb and <sup>210</sup>Po was performed following the steps of the complete schema shown in Fig. 1 and Table 2. First, the 2 mL columns of Sr resin were connected to a 12-hole vacuum box with a peristaltic pump and to a funnel. The conditioning step was then performed with 10 mL of a solution of 3 M HNO<sub>3</sub> before loading the sample solution with a flow rate of 1 mL min<sup>-1</sup>, in accordance with the protocol (steps I and II in Table 2). The retained polonium was then eluted with 10 mL of 8 M HNO<sub>3</sub> (step III). Afterwards the strontium was eluted with 10 mL of 0.05 M HNO<sub>3</sub> (step IV), and the lead was eluted with 10 mL of 0.06 M (NH<sub>4</sub>)<sub>2</sub>C<sub>2</sub>O<sub>4</sub> (step V).

**Fig. 1** Detailed schema of the sequential separation procedure for <sup>90</sup>Sr, <sup>210</sup>Pb and <sup>210</sup>Po in water samples by the Sr resin



\* ICP-MS measurements to calculate recovery of the extraction process.

**Table 2** Sequential extraction conditions for the separation of <sup>90</sup>Sr, <sup>210</sup>Pb and <sup>210</sup>Po using the Sr resin

| Step | Description    | Eluent or matrix | Concentration [mol L <sup>-1</sup> ] | Volume [mL] | Targeted radionuclide eluted |
|------|----------------|------------------|--------------------------------------|-------------|------------------------------|
| I    | Conditioning   | HNO <sub>3</sub> | 3                                    | 10          | —                            |
| II   | Sample loading | HNO <sub>3</sub> | 3                                    | 10          | —                            |
| III  | Po elution     | HNO <sub>3</sub> | 8                                    | 10          | <sup>210</sup> Po            |
| IV   | Sr elution     | HNO <sub>3</sub> | 0.05                                 | 10          | <sup>90</sup> Sr             |
| V    | Pb elution     | Ammonium oxalate | 0.06                                 | 10          | <sup>210</sup> Pb            |

Sample aliquots were also taken to determine stable strontium and lead content by means of ICP-MS and to calculate the recovery of the sequential separation process. The  $^{90}\text{Sr}$  and the  $^{210}\text{Pb}$  can be calculated using Eq. 3:

$$A = \frac{R_g - R_0}{\varepsilon * \eta * V * f_a} * K_w \quad (3)$$

where  $A$  is the radionuclide activity ( $\text{Bq L}^{-1}$ ),  $R_g$  is the gross count rate ( $\text{s}^{-1}$ ),  $R_0$  is the background count rate ( $\text{s}^{-1}$ ),  $\varepsilon$  is the counting efficiency,  $\eta$  is the chemical yield,  $V$  is the sample volume (L),  $f_a$  is the aliquot correction factor (the volume of the aliquot of Pb or Sr fraction divided by the volume of total eluted fraction) and  $K_w$  is the waiting time correction factor.

$^{210}\text{Po}$  was auto-deposited on a silver disk following a modified procedure previously published by our laboratory [27]. Auto-deposition was performed for 3 h at 85 °C in an 80 mL 2 M HCl solution under continuous stirring. Samples were counted for 300,000 s with a chamber pressure of  $10^{-2}$  Torr, and the radiochemical recovery was obtained by determining the  $^{209}\text{Po}$  tracer activity. The detection efficiencies, which were derived from the detector calibration using a stainless steel planchet with certified activities of  $^{233}\text{U}$ ,  $^{239/240}\text{Pu}$  and  $^{241}\text{Am}$ , ranged between 17.77% and 17.92%.

### Intercomparison samples

Two drinking water samples from intercomparison exercises organized by the Consejo de Seguridad Nuclear (CSN) (CSN-CIEMAT 2019) and the International Atomic Energy Agency (IAEA) (IAEA-TEL-2020–03) were analysed in order to test the proposed method in two activity ranges. The CSN-CIEMAT 2019 sample was a deionized water simulating drinking water with low-level activity of  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$ , among other radionuclides, with activity concentrations of  $7.54 \pm 0.50 \text{ Bq L}^{-1}$ ,  $0.39 \pm 0.30 \text{ Bq L}^{-1}$  and  $0.253 \pm 0.060 \text{ Bq L}^{-1}$  respectively. The IAEA-TEL-2020–03 was a tap water from Seibersdorf, Austria, with high-level activity values of  $^{210}\text{Pb}$  and  $^{210}\text{Po}$ , among other radionuclides, with activity concentrations of  $905 \pm 17 \text{ Bq L}^{-1}$  and  $921 \pm 20 \text{ Bq L}^{-1}$  respectively.

## Results and discussion

In the following section we present a novel sequential strategy for the separation of  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$ . This approach will be very useful to provide a rapid response in situations of emergency, for example when these particular radionuclides need to be determined in drinking water, since they are some of the contributors to the ID estimation. The evaluation of the radionuclide retention in a Sr resin


is performed using the chromatographic capacity factor to evaluate different experimental conditions. Lastly, under the optimum conditions found for the selective isolation of the three radionuclides evaluated, the method was validated with intercomparison samples.

### Batch study of $^{90}\text{Sr}$ , $^{210}\text{Pb}$ and $^{210}\text{Po}$ in Sr resin

In order to perform the batch study, different concentrations of  $\text{HNO}_3$  in the range from 1 to 4 M were employed to obtain optimal  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  retention in the Sr resin. The results can be seen in Fig. 2, which shows the  $k'$  values for all three elements when they are together in the same sample, simulating the worst scenario in which possible influence effects by competition between elements may occur.

It can be seen that strontium presented an increase in retention when a higher nitric acid concentration was used. For this radionuclide,  $k'$  values of approximately  $20 \text{ g mL}^{-1}$  were obtained for an  $\text{HNO}_3$  concentration of 1 M and  $60 \text{ g mL}^{-1}$  at an acid concentration of 4 M. These values are in line with those published previously by TrisKem International [23], where the  $k'$  value drops from almost  $90 \text{ g mL}^{-1}$  at 8 M  $\text{HNO}_3$  to less than  $1 \text{ g mL}^{-1}$  at 0.05 M  $\text{HNO}_3$ . Taking this into account and looking at Fig. 2, it can be concluded that the presence of 0.5 mg of Pb(II) and 0.01 Bq of  $^{209}\text{Po}$  has no effect on strontium resin retention.

As regards Pb, and as shown in Fig. 2, this element presented a good retention in all the acid concentrations tested. Indeed, its  $k'$  value slightly decreased from average values of 760 to 670  $\text{g mL}^{-1}$  with the increase in the acid concentration. This is in line with results previously obtained by other authors such as Kong et al. [18], who developed a method to determine  $^{210}\text{Bi}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  in seafood samples by using the same resin. In the case of  $^{210}\text{Pb}$ , these same authors reported that it was retained in  $\text{HNO}_3$  media, but the higher the nitric concentration, the lower the  $^{210}\text{Pb}$  Sr resin affinity.



**Fig. 2** Chromatographic capacity factors ( $k'$ ) of Sr(II), Pb(II) and  $^{209}\text{Po}$  together in a batch experiment



$^{210}\text{Po}$  presented a slight better retention in 3 M  $\text{HNO}_3$  with a  $k'$  value of  $11 \text{ g mL}^{-1}$  compared to the other acid molarities tested. Note that in 4 M  $\text{HNO}_3$ ,  $^{210}\text{Po}$  retention decreased. Although TrisKem reported better results in terms of  $k'$  for Po(IV) in a lower acidic range (0.5–1 M  $\text{HNO}_3$ ) than those obtained in our study [5], a number of published studies in the literature find results in line with ours [10, 14, 28]. In those cases the best performance for Po retention was also achieved for higher nitric concentrations to retain and selectively separate  $^{210}\text{Po}$  from the matrix and from other radionuclides. For example, Hurtado-Bermúdez et al. used a high nitric acid concentration, 8 M, in a study focusing on the separation of  $^{210}\text{Po}$  and  $^{90}\text{Sr}$  and their determination in the soft tissue of seafood samples such as oysters, mussels and sea urchins from the southern Spanish Atlantic coast [14].

Finally, taking into account all the results for  $k'$  for the three radionuclides under study, 3 M was the chosen molarity of the nitric acid solution for the sample loading and conditioning in the sequential separation procedure, being a compromise between all the values obtained and thus ensuring the optimal retention of each radionuclide in the Sr resin.

### Optimization of Sr resin separation parameters

An optimization of the different variables that affect the proposed strategy was carried out, including the volumes and concentrations of different reagents. Both the elution step and the conditions used were optimized, leading to good recoveries in a previous study performed in our laboratory [11]. 8 M  $\text{HNO}_3$ , 0.05 M  $\text{HNO}_3$  and 0.06 M ammonium oxalate were used to elute  $^{210}\text{Po}$ ,  $^{90}\text{Sr}$  and  $^{210}\text{Pb}$  respectively. The volume of  $^{90}\text{Sr}$  and  $^{210}\text{Pb}$  elution solution (10 mL) was the same we used in our laboratory to perform intercomparison exercises, obtaining recoveries of 70–80%. This volume is also in line with Dalencourt et al. [29], who reported efficient Pb elution with 10 mL of ammonium oxalate. In the

case of  $^{210}\text{Po}$ , a total volume of 10 mL of 8 M  $\text{HNO}_3$  was collected in 2 mL fractions to determine the minimum stripping volume required. The results obtained showed that, for 10 mL, over 80% of the initial polonium can be eluted.

In addition to optimizing the Sr resin separation parameters, all the elution fractions and wastes were analysed to determine the presence of  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  and to check there were not interferences in the measurements. As an example,  $^{210}\text{Po}$  not eluted (approximately 20%) remained in the waste of the sample loading, so no interference in the  $^{90}\text{Sr}$  measurement is expected.

### Method validation

This novel sequential separation of  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  was validated via an analysis in triplicate of water samples from two different intercomparison exercises organized by CSN-CIEMAT in 2019 and the IAEA in 2020. These samples contained  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  in different ranges of activity concentrations.

Table 3 shows the mean activity values obtained for  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  using the method developed in the present study and the certified values reported by the intercomparison exercise organizers. The values obtained generally agreed with the established values except for the IAEA-TEL-2020-03 sample in which  $^{210}\text{Po}$  was underestimated, probably due to a problem in connection with the stability of the sample. Nevertheless, the z-score value—which is a standard measure of laboratory systematic error calculated using the certified value and standard deviation of the exercise—was  $-1.4$ , indicating that the result obtained was satisfactory. In the case of the CSN-CIEMAT 2019 sample, the organizer stated that the  $^{210}\text{Pb}$  activity in the sample was not known. The certified value shown in the table is the average value obtained from all those reported by participants. The participants' results were widely dispersed and the CSN-CIEMAT communicated that the  $^{210}\text{Pb}$  activity

**Table 3** Results obtained for two intercomparison samples (CSN-CIEMAT 2019 and IAEA-TEL-2020-03)

| Sample           | Radionuclide      | Certified value [Bq L <sup>-1</sup> ] | Mean measured value of the present study (Bq L <sup>-1</sup> ) | % RSD | Z-score | Mean measured value obtained using conventional methods (Bq L <sup>-1</sup> ) | Z-score      |
|------------------|-------------------|---------------------------------------|--|-------|---------|---|--------------|
| CSN-CIEMAT 2019  | $^{90}\text{Sr}$  | $7.54 \pm 0.50$                       | $6.75 \pm 0.21$  | 16    | -0.9    | $6.88 \pm 0.27^a$   | -0.6         |
|                  | $^{210}\text{Pb}$ | $0.39 \pm 0.30$                       | $0.48 \pm 0.08$  | 12    | 0.3     | $0.20 \pm 0.08^a$   | -0.7         |
|                  | $^{210}\text{Po}$ | $0.25 \pm 0.06$                       | $0.28 \pm 0.06$  | 5     | 0.5     | $0.23 \pm 0.01^b$   | -0.3         |
| IAEA-TEL-2020-03 | $^{210}\text{Pb}$ | $905 \pm 34$                          | $1098 \pm 31$  | 9     | 1.4     | $826 \pm 45^a$<br>$876 \pm 11^c$  | -0.4<br>-0.2 |
|                  | $^{210}\text{Po}$ | $921 \pm 40$                          | $547 \pm 26$   | 5     | -1.4    | -   | -            |

<sup>a</sup>Sr resin + LSC

<sup>b</sup>Auto-deposition + alpha spectrometry

<sup>c</sup>Gamma spectrometry

concentration was not evaluable. Bearing all this in mind, the  $^{210}\text{Pb}$  activity concentration obtained agreed with the mean value reported by the CSN-CIEMAT.

The method's reproducibility, expressed as relative standard deviation (RSD), was evaluated by determining  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  activity concentrations on three consecutive days. The values obtained are also shown in Table 3.

Minimum detectable activity (MDA) is an important parameter for estimating the suitability of a method, and this was determined using the Curie definition. Table 4 shows the MDA calculated in the present study for a volume of 500 mL of water samples. It can be seen that the sequential method is suitable for determining  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  in fast response situations that require an ID such as MDA to be calculated for  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$ . These were 97.5%, 50% and 60% lower respectively than those established in RD 314/2016 [2].

The current method also showed improvements in the MDAs of  $^{90}\text{Sr}$  and  $^{210}\text{Pb}$  compared to the conventional methods used in the laboratory as regards the quantity of sample volume needed and the time spent on sample pretreatment and radionuclide separation. The sample volume required in the present method is three times lower than that required to

determine the three radionuclides by conventional methods. For example, in our laboratory a volume of 4 L is required to determine  $^{210}\text{Po}$  in water samples [27]. We could also save around 24 h in terms of sample pretreatment.

As can be observed in Table 5, different figures of merit such as sample volume, analysis time and MDA can be compared between the present study and other methods previously published in the literature that have focused on determining  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  in water samples. In the case of MDA, the results obtained in this study are comparable with others that require higher water volumes to perform the radionuclide determination. While the methodology presented by Villa et al. [17] was able to achieve the lowest MDA, this was done by pretreating large water volumes (30 L), which is more time-consuming and tedious. Lluch et al. [30] developed a method based on PS resin that combined the separation and detection steps. Although this strategy had only been applied on spiked environmental water samples, the MDA presented did not represent a water sample with environmental activity levels. Finally, most of the studies presented in the literature do not specify how long it takes for the analysis to be carried out. However, one might expect that, due to the large volume samples handled, it would require high turnaround times. The method we present in this study took about 4 h to separate the radionuclides, which is suitable for rapid response situations.

**Table 4** Minimum detectable activities of  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  achieved in the present study, those achieved using conventional methods and the rates laid down in RD 314/2016

| Matrix | Radionuclide      | MDA in present study [Bq L <sup>-1</sup> ] | MDA conventional methods [Bq L <sup>-1</sup> ] | MDA in RD 314/2016 [Bq L <sup>-1</sup> ] |
|--------|-------------------|--|--|--|
| Water  | $^{90}\text{Sr}$  | 0.01                                       | 0.01   | 0.4                                      |
|        | $^{210}\text{Pb}$ | 0.01                                       | 0.01   | 0.02                                     |
|        | $^{210}\text{Po}$ | 0.004                                      | 0.004  | 0.01                                     |

## Conclusions

The proposed strategy for sequentially separating and determining  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  using an extraction chromatographic Sr resin was successfully applied for the first time. The sequential separation of these three radionuclides was performed using 3 M  $\text{HNO}_3$  as the optimal solution to

**Table 5** Comparison of studies based on  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  separation and determination in water samples

| Reference  | Sample volume [L] | Separation method                  | Radionuclides     | Carrier                       | Pretreatment time [h] | Measurement time [h] | MDA [mBq L <sup>-1</sup> ] |
|------------|-------------------|------------------------------------|-------------------|-------------------------------|-----------------------|----------------------|----------------------------|
| [17]       | 30                | Sr resin                           | $^{210}\text{Pb}$ | 20–30 mg Pb(II)               | n.s.                  | 10                   | 0.12                       |
|            |                   |                                    | $^{210}\text{Po}$ | 0.1–0.2 mBq $^{209}\text{Po}$ | n.s. <sup>a</sup>     | n.s.                 | 0.005                      |
| [27]       | 4                 | Co-precipitation in hydroxide form | $^{210}\text{Po}$ | 0.01 Bq $^{209}\text{Po}$     | 30                    | 83                   | 0.1                        |
| [30]       | 0.01              | Ps resin                           | $^{210}\text{Pb}$ | 0.36 mg Pb(II)                | n.s.                  | 1 <sup>c</sup>       | 28                         |
| This study | 0.5               | Sr resin                           | $^{90}\text{Sr}$  | 0.5 mg Sr(II)                 | 4 <sup>b</sup>        | 16                   | 10                         |
|            |                   |                                    | $^{210}\text{Pb}$ | 0.5 mg Pb(II)                 |                       | 16                   | 10                         |
|            |                   |                                    | $^{210}\text{Po}$ | 0.01 Bq $^{209}\text{Po}$     |                       | 83                   | 4                          |

<sup>a</sup>Plus 6 h for  $^{210}\text{Po}$  auto-deposition

<sup>b</sup>Plus 3 h for  $^{210}\text{Po}$  auto-deposition

<sup>c</sup>Measurement of spiked water samples

n.s. not specified

condition and load the sample and determine good retention of the radionuclides under study.

It was applied to two intercomparison water samples and obtained good reproducibility values and low minimum detection activities. The present approach could therefore be an interesting alternative for separating and determining  $^{90}\text{Sr}$ ,  $^{210}\text{Pb}$  and  $^{210}\text{Po}$  in water samples compared to conventional methods. It has the advantage in terms of rapid response and would be useful in emergency situations.

**Acknowledgements** The authors would like to thank the Consorci d'Aigües de Tarragona (CAT) for their invaluable cooperation.

**Funding** Open Access funding provided thanks to the CRUE-CSIC agreement with Springer Nature.

## Declarations

**Conflict of interest** The authors declare that they have no conflict of interests.

**Open Access** This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

## References

- Diario Oficial de la Unión Europea (2020) Directiva (UE) 2020/2184 del Parlamento Europeo y del Consejo de 16 de diciembre de 2020 relativa a la calidad de las aguas destinadas al consumo humano
- RD 314/2016 (2016) Real Decreto 314/2016, de 29 de julio, por el que se modifican el Real Decreto 140/2003, de 7 de febrero, por el que se establecen los criterios sanitarios de la calidad del agua de consumo humano, el Real Decreto 1798/2010, de 30 de diciembre, por el que se regula la explotación y comercialización de aguas minerales naturales y aguas de manantial envasadas para consumo humano, y el Real Decreto 1799/2010, de 30 de diciembre, por el que se regula el proceso de elaboración y comercialización de aguas preparadas envasadas para el consumo humano. Boletín Oficial del Estado, número 183. Madrid, 30 de julio de 2016
- European Commission (2013) Council Directive 2013/51/EUR-ATOM of 22 October 2013 laying down requirements for the protection of the health of the general public with regard to radioactive substances in water intended for human consumption
- Szabo Z, Stackelberg PE, Cravotta CA (2020) Occurrence and geochemistry of Lead-210 and Polonium-210 radionuclides in public-drinking-water supplies from principal aquifers of the united states. *Environ Sci Technol* 54:7236–7249. <https://doi.org/10.1021/acs.est.0c00192>
- Thakur P, Ward AL (2020) 210Po in the environment: insight into the naturally occurring polonium isotope. *J Radioanal Nucl Chem* 323:27–49. <https://doi.org/10.1007/s10967-019-06939-2>
- Shao Y, Yang G, Tazoe H et al (2018) A review of measurement methodologies and their applications to environmental 90Sr. *J Environ Radioact* 192:321–333. <https://doi.org/10.1016/j.jenvrad.2018.07.013>
- El Afifi EM, Borai EH (2006) Performance characteristics of sequential separation and quantification of lead-210 and polonium-210 by ion exchange chromatography and nuclear spectrometric measurements. *J Environ Qual* 35:568–574. <https://doi.org/10.2134/jeq2005.0223>
- Vajda N, Kim CK (2010) Determination of radiostrontium isotopes: a review of analytical methodology. *Appl Radiat Isot* 68:2306–2326. <https://doi.org/10.1016/j.apradiso.2010.05.013>
- Dianu AM, Dobrin RI (2020) Separation and quantification of 90Sr from ion-exchange resin radioactive waste: methods and techniques of analysis. *Radiochim Acta* 108:627–640. <https://doi.org/10.1515/ract-2019-3213>
- Hurtado-Bermúdez S, Mas JL (2019) Determination of 210Po in low-level wild bilberries reference material for quality control assurance in environmental analysis using extraction chromatography and  $\alpha$ -particle spectroscopy. *Radiochim Acta* 108:99–103. <https://doi.org/10.1515/ract-2019-3141>
- Mola M, Avivar J, Nieto A et al (2014) Determination of 90Sr and 210Pb in sludge samples using a LOV-MSFIA system and liquid scintillation counting. *Appl Radiat Isot* 86:28–35. <https://doi.org/10.1016/j.apradiso.2013.11.123>
- Nonova T, Tosheva Z (2016) 90Sr, 210Pb, 210Po and Ra isotopes in marine macroalgae and mussel *Mytilus galloprovincialis* from the Bulgarian Black Sea zone. *J Radioanal Nucl Chem* 307:1183–1194. <https://doi.org/10.1007/s10967-015-4502-x>
- Landstetter C, Sinojmeri M, Katzlberger C, Achatz A (2014) Determination of 90Sr and 210Pb in freshwater fish in Austria. *J Radioanal Nucl Chem* 299:787–790. <https://doi.org/10.1007/s10967-013-2700-y>
- Hurtado-Bermúdez S, Mas JL, Villa-Alfageme M (2017) A sequential determination of 90Sr and 210Po in food samples. *Food Chem* 229:159–164. <https://doi.org/10.1016/j.foodchem.2017.02.077>
- Ozden B, Vaasma T, Kiisk M, Tkaczyk AH (2017) A modified method for the sequential determination of 210Po and 210Pb in Ca-rich material using liquid scintillation counting. *J Radioanal Nucl Chem* 311:365–373. <https://doi.org/10.1007/s10967-016-4984-1>
- Vajda N, LaRosa J, Zeisler R et al (1997) A novel technique for the simultaneous determination of 210Pb and 210Po using a crown ether. *J Environ Radioact* 37:355–372. [https://doi.org/10.1016/S0265-931X\(95\)00059-J](https://doi.org/10.1016/S0265-931X(95)00059-J)
- Villa-Alfageme M, Mas JL, Hurtado-Bermudez S, Masqué P (2016) Rapid determination of 210Pb and 210Po in water and application to marine samples. *Talanta* 160:28–35. <https://doi.org/10.1016/j.talanta.2016.06.051>
- Kong X, Yin L, Ji Y (2021) Simultaneous determination of 210Pb and 210Po in seafood samples using liquid scintillation counting. *J Environ Radioact* 231:106553. <https://doi.org/10.1016/j.jenvrad.2021.106553>
- Miura T, Hayano K, Nakayama K (1999) Determination of 210Pb and 210Po in environmental samples by alpha ray spectrometry using an extraction chromatographic resin. *Anal Sci* 15:23–28. <https://doi.org/10.2116/analsci.15.23>
- Fan F, Liu H, Liang J et al (2020) Rapid separation of Po-210 from Pb-210 based on the usage of a commercial Sr-Specific chromatographic resin. *J Environ Radioact* 211:106083. <https://doi.org/10.1016/j.jenvrad.2019.106083>



21. Pan LJ, Yu GB, Chen Z et al (2018) A modified sampling preparation method for rapid determination of Pb-210 radioactivity in plants in China using crown ether and liquid scintillation counting of beta particles. *J Radioanal Nucl Chem* 317:565–570. <https://doi.org/10.1007/s10967-018-5919-9>
22. McLain DR, Liu C, Sudowe R (2018) Using Sr Resin with mixed acid matrices. *J Radioanal Nucl Chem* 316:485–490. <https://doi.org/10.1007/s10967-018-5778-4>
23. Eichrom Technologies (2021) Sr resin. <https://www.eichrom.com/eichrom/products/sr-resin/>. Accessed 2 Mar 2021
24. Horwitz EP (2018) The Capacity Factor ( $k'$ ): How it is measured and what it does not tell you. [https://www.eichrom.com/wp-content/uploads/2018/02/the\\_capacity\\_factor.pdf](https://www.eichrom.com/wp-content/uploads/2018/02/the_capacity_factor.pdf). Accessed 2 Mar 2021
25. Triskem International (2015) Sr resin. Product Sheet. [https://www.triskem-international.com/scripts/files/5f463447ad4026.94629022/PS\\_SR-Resin\\_EN\\_160927.pdf](https://www.triskem-international.com/scripts/files/5f463447ad4026.94629022/PS_SR-Resin_EN_160927.pdf). Accessed 2 Mar 2021
26. Palomo M, Villa M, Casacuberta N et al (2011) Evaluation of different parameters affecting the liquid scintillation spectrometry measurement of gross alpha and beta index in water samples. *Appl Radiat Isot* 69:1274–1281. <https://doi.org/10.1016/j.apradiso.2011.04.020>
27. Fonollosa E, Peñalver A, Aguilar C, Borrull F (2015) Polonium-210 levels in different environmental samples. *Environ Sci Pollut Res* 22:20032–20040. <https://doi.org/10.1007/s11356-015-5158-3>
28. Horwitz EP, Chiarizia R, Dietz L (1992) A novel strontium-selective extraction chromatographic resin. *Solvent Extraction Ion Exch* 10:313–336. <https://doi.org/10.1080/07366299208918107>
29. Dalencourt C, Chabane MN, Tremblay-Cantin JC, Larivière D (2020) A rapid sequential chromatographic separation of U- and Th-decay series radionuclides in water samples. *Talanta* 207:120282. <https://doi.org/10.1016/j.talanta.2019.120282>
30. Lluch E, Barrera J, Tarancón A et al (2016) Analysis of  $^{210}\text{Pb}$  in water samples with plastic scintillation resins. *Anal Chim Acta* 940:38–45. <https://doi.org/10.1016/j.aca.2016.08.004>

**Publisher's Note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.